






10.1.2 Multilayer pipe pre-insulated

TYPE: ISO Pre-insulated (Coil)






COIL: 6MM INSULATED					
d	di	D	s	sa	LR
mm	mm	mm	mm	mm	
14	10	26	2	0,4	100 M
16	12	28	2	0,4	100 M
18	14	30	2	0,4	50 M
20	16	32	2	0,4	50 M
26	20	38	3	0,5	25-50 M
32	26	44	3	0,7	25 M

COIL: 10MM INSULATED					
d	di	D	s	sa	LR
mm	mm	mm	mm	mm	
14	10	34	2	0,4	50 M
16	12	36	2	0,4	50 M
18	14	38	2	0,4	50 M
20	16	40	2	0,4	50 M
26	20	46	3	0,5	25 M

COIL: 13 MM INSULATED					
d	di	D	s	sa	LR
mm	mm	mm	mm	mm	
16	12	42	2	0,4	50 M
20	16	46	2	0,4	50 M
26	20	52	3	0,5	50 M

TYPE: ISO-EXZ Pre-insulated eccentrically (Coil)



COIL ECCENTRICALLY: 13 MM UNDER AND 6 MM ABOVE						
d	di	D1	D2	s	sa	LR
mm	mm	mm	mm	mm	mm	
16	12	40	40	2	0,4	50 M
18	14	40	40	2	0,4	50 M
20	16	40	40	2	0,4	25 M
26	20	50	52	3	0,5	25 M

COIL ECCENTRICALLY: 26 MM UNDER AND 6 MM ABOVE						
d	di	D1	D2	s	sa	LR
mm	mm	mm	mm	mm	mm	
16	12	40	53	2	0,4	25 M
20	16	40	53	2	0,4	25 M
26	20	50	65	3	0,5	25 M

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13